

Q8 Formula F1 10W-60

Description

Supreme Performance Synthetic Engine Oil

Application

- Extra high performance synthetic engine oil for passenger cars with normally aspirated or turbo charged gasoline or diesel engines.
- Specially recommended for highest performance, multi-valve engines with catalyst.

Specifications

- ACEA A3/B4
- Special Racing oil

Benefits

- Synthetic year round engine lubricant
- Excellent engine protection after cold starting
- Superior engine performance at extreme driving conditions
- Provides sustained high oil pressure
- Offers high oil film strength and thus limiting engine wear
- Good protection against rust and corrosion
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Reduced environmental impact
- Prevents formation of black sludge
- Catalyst friendly lubricant

Properties	Method	Unit	Typical
Viscosity Grade			SAE 10W-60
Absolute Density, 15 °C	D 4052	kg/m ³	875
Kinematic Viscosity, 100 °C	D 445	mm ² /s	23.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	162
Viscosity Index	D 2270		171
Apparent Viscosity, -25 °C	IP 383	mPa.s	6600
Borderline Pumping Temperature	D 3829	°C	-27
Pour Point	D 97	°C	-24
Flash Point	D 93	°C	215
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=5.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

